













EQUIPMENT	INTERIOR DIMENSIONS*	DOOR OPENING	TOP OPENING	TARE WEIGHT**	CUBIC CAPACITY	PAYLOAD***
20' Dry Freight	 L: 592 cm. 233 in. W: 234 cm. 92 in. H: 238 cm. 94 in.	W: 229 cm. 90 in. H: 228 cm. 90 in.	n/a	1,900 kg. 4,189 lbs.	33.0 cbm. 1,165 cu. ft.	22,100 kg. 48,721 lbs.
40' Dry Freight	 L: 1,205 cm. 474 in. W: 234 cm. 92 in. H: 238 cm. 94 in.	W: 228 cm. 90 in. H: 228 cm. 90 in.	n/a	3,084 kg. 6,799 lbs.	673 cbm. 2,377 cu. ft.	27,396 kg. 60,397 lbs.
40' High Cube Dry	 L: 1,206 cm. 475 in. W: 235 cm. 92 in. H: 268 cm. 106 in.	W: 234 cm. 92 in. H: 259 cm. 102 in.	n/a	2,900 kg. 6,393 lbs.	76.0 cbm. 2,684 cu. ft.	29,600 kg. 65,265 lbs.
45' High Cube Dry	 L: 1,358 cm. 535 in. W: 235 cm. 92 in. H: 269 cm. 106 in.	W: 234 cm. 92 in. H: 259 cm. 102 in.	n/a	3,900 kg. 8,598 lbs.	85.7 cbm. 3,025 cu. ft.	28,600 kg. 63,052 lbs.
20' Reefer	 L: 543 cm. 214 in. W: 227 cm. 89 in. H: 224 cm. 88 in.	W: 229 cm. 90 in. H: 219 cm. 86 in.	n/a	2,940 kg. 6,482 lbs.	27.5 cbm. 971 cu. ft.	24,060 kg. 53,043 lbs.
40' Reefer	 L: 1,121 cm. 441 in. W: 225 cm. 88 in. H: 218 cm. 86 in.	W: 222 cm. 87 in. H: 212 cm. 83 in.	n/a	4,840 kg. 10,670 lbs.	54.9 cbm. 1,939 cu. ft.	25,640 kg. 56,526 lbs.
40' High Cube Reefer	 L: 1,163 cm. 458 in. W: 229 cm. 90 in. H: 251 cm. 99 in.	W: 229 cm. 90 in. H: 254 cm. 100 in.	n/a	4,430 kg. 9,766 lbs.	66.9 cbm. 2,363 cu. ft.	28,070 kg. 61,883 lbs.
45' High Cube Reefer	 L: 1,310 cm. 516 in. W: 229 cm. 90 in. H: 254 cm. 99 in.	W: 229 cm. 90 in. H: 228 cm. 100 in.	n/a	5,200 kg. 11,464 lbs.	75.4 cbm. 2,663 cu. ft.	27,300 kg. 60,186 lbs.
20' Open Top	 L: 592 cm. 233 in. W: 234 cm. 92 in. H: 229 cm. 90 in.	W: 229 cm. 90 in. H: 225 cm. 89 in.	L: 543 cm. 214 in. W: 222 cm. 87 in.	2,174 kg. 4,793 lbs.	31.6 cbm. 1,116 cu. ft.	21,826 kg. 48,117 lbs.
40' Open Top	 L: 1,204 cm. 474 in. W: 234 cm. 92 in. H: 227 cm. 89 in.	W: 228 cm. 90 in. H: 228 cm. 90 in.	L: 1,159 cm. 456 in. W: 216 cm. 85 in.	4,300 kg. 9,480 lbs.	64 cbm. 2,260 cu. ft.	26,181 kg. 57,720 lbs.
20' Flat Rack	 L: 566 cm. 223 in. W: 244 cm. 96 in. H: 233 cm. 92 in.	n/a	n/a	2,530 kg. 5,578 lbs.	n/a	21,470 kg. 47,333 lbs.
40' Flat Rack	 L: 1,208 cm. 476 in. W: 244 cm. 96 in. H: 210 cm. 83 in.	n/a	n/a	5,480 kg. 12,081 lbs.	n/a	25,000 kg. 55,115 lbs.

*Container specifications may vary slightly depending on the steamship line or manufacturer. | **Tare weight differentiates within equipment series. | ***Payload subject to legal road weight limitations. Equipment is subject to availability. Not all types of equipment are available in all trade lanes.